

53

SPARK

Light Reflectance Value (LRV) is the total quantity of visible and usable light that is reflected by a surface (e.g. flooring, walls, furniture, ...) in all directions and at all wavelengths when illuminated by a light source.

LRV is a measurement that indicates how much light a surface **reflects**, and conversely how much it **absorbs**. LRV runs on a scale from 0% to 100%, 0% being a perfectly absorbing surface (black) up to 100% being a perfectly reflective surface (white). Additional to the colour of the surface, structure and gloss are factors that influence the light reflectance value.

The LRV certificates of all modulyss® products are awarded by **CSTB** which executes the measurement according to the **EN 410** and **EN 14500** standard.

The **L-value**, which is the colour depth, is used to calculate visual contrast. However this should not be mixed up with the LRV as the L-value is significantly higher. This is tested in accordance with the **EN ISO 11664-4** standard.

Light Reflectance Values

COLOR	LRV	L
102	28	60
140	20	51
306	4	23
313	6	28
352	5	26
398	5	25
482	5	25
511	7	30
530	10	38
550	4	23
579	5	25

COLOR	LRV	L
581	5	26
609	6	27
812	6	27
847	9	36
866	7	30
907	5	27
932	16	47
961	9	36
989	8	33
994	11	39